

Available online at www.sciencedirect.com



Journal of Magnetic Resonance 176 (2005) 125-139



www.elsevier.com/locate/jmr

NMR detection using laser-polarized xenon as a dipolar sensor

J. Granwehr, J.T. Urban, A.H. Trabesinger¹, A. Pines^{*}

Materials Sciences Division, Lawrence Berkeley, National Laboratory, Department of Chemistry, University of California, Berkeley, CA 94720, USA

Received 1 March 2005; revised 16 May 2005 Available online 7 July 2005

Abstract

Hyperpolarized ¹²⁹Xe can be used as a sensor to indirectly detect NMR spectra of heteronuclei that are neither covalently bound nor necessarily in direct contact with the Xe atoms, but coupled through long-range intermolecular dipole–dipole interactions. To reintroduce long-range dipolar couplings the sample symmetry has to be broken. This can be done either by using an asymmetric sample arrangement, or by breaking the symmetry of the spin magnetization with field gradient pulses. Experiments are performed where only a small fraction of the available ¹²⁹Xe magnetization is used for each point, so that a single batch of xenon suffices for the point-by-point acquisition of a heteronuclear NMR spectrum. Examples with ¹H as the analyte nucleus show that these methods have the potential to obtain spectra with a resolution that is high enough to determine homonuclear J couplings. The applicability of this technique with remote detection is discussed.

Published by Elsevier Inc.

PACS: 07.05.Fb; 07.05.Kf; 76.60.Jx

Keywords: NMR; Distant dipolar field; Long-range dipolar couplings; Intermolecular multi-quantum coherences; Indirect detection; Remote detection; Hyperpolarized xenon; Sensitivity

1. Introduction

In recent years, it was shown that hyperpolarized xenon is an exquisitely sensitive sensor of its direct environment [1]. Applications of xenon as a probe typically require it to be either bound to, adsorbed on [2,3], or in sufficient proximity [4,5] to the analyte. Alternatively, supramolecular cages can be synthesized with a large affinity to bind Xe, where the specificity for a certain target comes from a ligand that is connected to the cage through a linker fragment [6]. Most of these experiments capitalize on changes of the xenon electron cloud that are reflected in changes in xenon chemical shift and/or relaxation behavior. More specific information can be ob-

E-mail address: pines@cchem.berkeley.edu (A. Pines).

tained when xenon is involved in the relaxation of the analyte to be probed [7]. The SPINOE technique yields direct quantitative measures about NMR active nuclei in the local chemical environment of Xe. However, all the aforementioned applications require either solubility of xenon in the analyte [7] (or the analyte in xenon [8]), affinity of xenon to binding sites [6,9–11], or direct physical interaction [4,12].

Another recent application of hyperpolarized xenon gas is its use as an information carrier in experiments with remote detection of NMR. Remote detection is a technique to separate encoding and detection in an NMR experiment temporally and spatially to optimize both steps independently [13]. Information about an analyte is encoded into the spin magnetization of a mobile carrier, which then is moved to a detector that can read out this magnetization with high sensitivity. Remote detection has been applied successfully to measure the chemical shift of ¹²⁹Xe on the surface of a porous

^{*} Corresponding author. Fax: +1 510 486 5744.

URL: http://waugh.cchem.berkeley.edu (A. Pines).

¹ Present address: Physical Chemistry Laboratory, ETH Zürich, 8093 Zürich, Switzerland.

^{1090-7807/\$ -} see front matter. Published by Elsevier Inc. doi:10.1016/j.jmr.2005.05.013

material, and for imaging at low and at high magnetic fields [14]. However, so far there is no experiment that encodes the NMR spectrum of a heteronucleus, especially not when the sensor and the analyte are not in direct contact with each other.

An independent field of research that attracted considerable attention during the last decade involves distant dipolar fields (DDF) in liquids [15] and their application to studies of the physiochemical environment of a molecule. Warren and co-workers [16] showed that interactions can be established between nuclei with high gyromagnetic ratios γ , separated on a meso- to macroscopic scale, up to the order of 1 mm. This allowed them to correlate signals between molecules that were located in separate containers. As dipolar couplings are mediated through space, the only necessary requirement is that the two nuclear species are sufficiently close; they do not need to be bonded or involved in the relaxation of each other. Past studies have almost exclusively focused on protonated liquids. Only a few groups have explored heteronuclear distant dipolar couplings, mainly towards the end of indirect detection schemes for rare nuclei via their solvent to surpass the sensitivity of direct detection [17–21]. A notable attempt to use xenon for indirect detection of CH₄ gas in a xe non/CH_4 gas mixture can be found in [19,22].

In this work, we combine the high signal intensity of laser-polarized ¹²⁹Xe with the freedom of choice of sample composition offered by correlating signal over meso- to macroscopic scales via distant dipolar couplings. We spatially and spectrally correlate the signal of gaseous xenon in a sealed sample tube with the nuclei of the surrounding liquid. The experiments reported here demonstrate the possibility of using hyperpolarized xenon not only as a probe of its direct environment, but extends its applicability beyond the microscopic scale. These experiments can also be seen as a useful complement-in the sense of adding spectral information-to two recently proposed experiments which use dipolar fields for local magnetometry. In [23], ¹H and ¹³C resonances of chloroform dissolved in liquid xenon were used for quantitative measurements of xenon magnetization; in [24] it is proposed to use ³He gas in lung tissue to measure and quantify susceptibility changes in nearby blood vessels upon loading them with paramagnetic contrast agents.

The results of the present study are then used to assess the feasibility of experiments where the encoding of a heteronuclear NMR spectrum into xenon magnetization is combined with remote detection, and potential benefits of such an approach are discussed.

2. Theory

The theory of distant dipolar field effects in NMR has been worked out by several groups. The most relevant work with regard to our experiments was done in the Warren group [20,21,25,26]. We summarize the equations required to understand the characteristic features of the experiments presented in this article in the case of liquids. We also comment on some sensitivity-related aspects that are important for a possible application of this approach with remote detection, especially the importance of multiplicative (or t_1) noise. Furthermore the influence of self-diffusion is analyzed, which is a more important issue when working with gases than in the case of liquids.

2.1. Signal in a DDF experiment

The magnetic field, which is given by

$$\mathbf{B} = \mu_0(\mathbf{H} + \mathbf{M}) = \mathbf{B}_0 + \mathbf{B}_d,\tag{1}$$

depends not only on **H**, but also on the magnetization density $\mathbf{M} = \sum_i \langle \boldsymbol{\mu}_i \rangle / V$ of the sample, where the $\langle \boldsymbol{\mu}_i \rangle$ are the magnetic moments of the individual spins. \mathbf{B}_d is called the dipolar demagnetizing field of the sample. High-field NMR studies in the presence of a large applied magnetic field $\mathbf{B}_0 = B_0 \tilde{\mathbf{z}}$ are not sensitive to the entire \mathbf{B}_d , only the secular components are retained. We consider a two-spin system where spin S = 1/2 shall be the analyte spin, and spin I = 1/2 is the sensor spin, which is hyperpolarized ¹²⁹Xe in our case. The magnitude of the total spin magnetization density before any radio frequency (rf) irradiation is

$$M_{0} = M_{0}^{I} + M_{0}^{S} = \frac{\hbar}{2} (N_{I} \gamma_{I} P_{I} + N_{S} \gamma_{S} P_{S}), \qquad (2)$$

where $N_{I,S}$ is the number density and $P_{I,S}$ is the spin polarization of the *I*,*S* spins, respectively. While P_S is given by the Boltzmann law, which is $P_S = |\gamma_S| \hbar B_0/2kT$ within the high temperature approximation, the polarization P_I of the ¹²⁹Xe is determined by the efficiency of the spin-exchange optical pumping process and can exceed 0.5 under optimal conditions [27].

If the sample is spherical and magnetically isotropic, i.e., if the magnetization is uniform throughout the sample, dipolar interactions sum to zero. But to conclude that dipolar interactions are negligible because of the r^{-3} dependence is wrong, because the number of spins at a given distance increases with r^2 . The sum of all dipolar interactions on a given spin only falls off with r^{-1} , and long-range dipolar interactions have to be considered whenever the magnetization of the sample is a function of location. By neglecting molecular diffusion (which can cause a redistribution of the sample magnetization), by assuming that the relevant nuclear magnetization $\mathbf{M}(s,t)$ arises from a single line S spectrum and a single line I spectrum, and if the spatial distribution of $\mathbf{M}(s, t)$ is only along $\tilde{\mathbf{z}}$, the equation of motion of magnetization in the absence of an rf excitation can be written as

$$\frac{\partial}{\partial t}\mathbf{M}(s,t) = \mathbf{M}(s,t) \times \gamma \{\mathbf{B}_0 + G_z(t)s\tilde{\mathbf{z}} + \mathbf{B}_d(s,t) + \mathbf{B}_r(t) + \mathbf{B}_n(s,t)\} - \mathbf{R}(\mathbf{M}(s,t) - \mathbf{M}_0), \quad (3)$$

where $G_z(t) = \partial B_z/\partial z$ is a pulsed linear field gradient along \tilde{z} , s is the position of a magnetization volume element along \tilde{z} , **R** is the relaxation matrix, $\mathbf{B}_r(t)$ is the radiation damping field, which is generated by currents induced in the rf coils by the precessing magnetization, and $\mathbf{B}_n(s, t)$ includes environmental and instrumental magnetic noise and inhomogeneities.

The sequence using gradient pulses to break the symmetry of the sample is shown in Fig. 1. The first gradient pulse leads to a helical distribution of the analyte magnetization along z

$$M^{S+}(t_1, s) = M_x^S(t_1, s) + iM_y^S(t_1, s)$$

= $\tilde{M}^{S+}(t_1) \exp(-i\gamma_S G_z T s),$ (4)

where $\tilde{M}^{S^+}(t_1)$ is the *S* magnetization in the absence of a gradient pulse, and *T* is the length of the gradient pulse. Afterwards, a $\pi/2$ pulse is applied on *S*, and simultaneously a tipping pulse with flip angle β is applied on *I*. The *S* pulse stores one component of M^{S^+} (e.g., M_x^S in case of a *y* pulse [28]) as longitudinal magnetization, M_z^S . This polarization creates a spatially modulated $\mathbf{B}_d(s)$ along $\tilde{\mathbf{z}}$, which acts on the precessing sensor magnetization M^{I^+} .

If the spin density is uniform and the magnetization varies only in a single direction \tilde{s} , modulated over distances much smaller than the smallest sample dimensions so that edge effects can be neglected, the secular contribution of the resulting dipolar field seen by a heteronucleus has an effective value of [20]

$$\mathbf{B}_{\mathrm{d}}(s) = \mu_0 \Delta_s \frac{2M_z(s)\tilde{\mathbf{z}}}{3},\tag{5}$$



Fig. 1. Pulse sequence of a DDF-detected NMR experiment. *S* denotes the analyte nucleus of interest. *I* is the sensor spin—in our case ¹²⁹Xe. A first gradient pulse G_z along the axis of the static magnetic field is applied right before the second $\pi/2$ pulse on *S*, and a second G_z pulse follows the pulse on *I* with a flip angle $\beta \ll \pi/2$.

where $\Delta_S = [3(\tilde{\mathbf{s}} \cdot \tilde{\mathbf{z}})^2 - 1]/2$. If $\tilde{\mathbf{s}}$ and $\tilde{\mathbf{z}}$ are parallel, then $\Delta_S = 1$. If $\mathbf{B}_d(s, t)$, $\mathbf{B}_r(t)$, and $\mathbf{B}_n(s, t)$ are very small compared to \mathbf{B}_0 , it is convenient to use a frame of reference rotating at the angular velocity $\omega_0 = -\gamma B_0$. At $t_2 = 0$ after the second $\pi/2$ pulse on the *S* and the β pulse on the *I* spins, assuming all pulses to be *y* pulses, the signal contributing components of the magnetization are:

$$M_z^S(s) = M_0^S \exp(-t_1/T_2^S) \cos(\Delta \omega_S t_1 - \gamma_S G_z T_S), \qquad (6)$$

$$M^{I+}(0^{+}) = M^{I}_{x} = M^{I}_{0}\sin(\beta)$$
(7)

with the resonance offset $\Delta \omega_S = \omega_S - \omega_{0,S}$, and the transverse relaxation time T_2^S of the S spins. If S and I spins are in different containers, the spatial distribution of $B_{\rm d}$ of the S spins as seen by the I spins is not simply given by Eq. (5), but also depends on the sample geometry and the pitch $\lambda = 2\pi/(\gamma G_z T)$ of the analyte magnetization helix. The configuration used for the experiments consists of a sample tube containing the xenon inside a larger tube with the analyte. If λ is smaller than the diameter of the inner sample tube, the spatial distribution of $B_{\rm d}$ gets cancelled out, leading to a reduced dipole-dipole interaction between the analyte and the sensor spins. The effect of λ on the signal is easy to determine experimentally. It is also possible to calculate it numerically, but it is difficult to assess analytically. Therefore we will just summarize the theory for a homogeneous mixture of analyte and sensor medium in order to obtain an upper limit for the achievable signal.

 λ shall be small compared to the smallest sample dimensions, so that Eq. (5) is valid, but large enough that we can neglect diffusion. This is usually not a very severe restriction for liquids, but it typically is a major limitation for gases, which will be discussed separately. With this assumption, the sensor magnetization after the second gradient pulse and precession during t_2 becomes

$$M^{I+}(s) = M_0^I \sin(\beta) \exp\left(-\frac{t_2}{T_2^I}\right) \\ \times \exp\left[i\left\{\Delta\omega_I t_2 - \gamma_I G_z NTs - \frac{2}{3}\gamma_I \mu_0 M_0^S\right. \\ \left. \times \exp\left(-\frac{t_1}{T_2^S} - \frac{t_2}{T_1^S}\right) \cos(\Delta\omega_S t_1 - \gamma_S G_z Ts) t_2\right\}\right].$$
(8)

If T_1^s would be infinite, we could use the Jacobi–Anger expansion

$$\exp(ix\cos\varphi) = \sum_{k=-\infty}^{\infty} i^k J_k(x) \exp(ik\varphi), \qquad (9)$$

where J_n is the Bessel function of the first kind of order *n*. If we assume for now that the analyte longitudinal relaxation is slow such that $t_2 \ll T_1^S$ and $\exp(-t_2/T_1^S)$ is approximately constant during t_2 , we can apply the expansion into Bessel functions and then analyze the effect of relaxation in a separate step. Let us therefore substitute $M_{\tau}^{S} \equiv M_{0}^{S} \exp(-t_{1}/T_{2}^{S} - t_{2}/T_{1}^{S})$ and $M_{\tau}^{I} \equiv M_{0}^{I} \exp(-t_{2}/T_{2}^{I})$, which also helps to simplify the following expressions. The observable *I* magnetization now becomes

$$M^{I+}(s) = M^{I}_{\tau} \sin(\beta) \exp(i\Delta\omega_{I}t_{2})$$

$$\times \sum_{k=-\infty}^{\infty} i^{k} J_{k} \left(-\frac{2}{3}\gamma_{I}\mu_{0}M^{S}_{\tau}t_{2}\right)$$

$$\times \exp[i(k\Delta\omega_{S}t_{1} - (k\gamma_{S} + N\gamma_{I})G_{z}Ts)].$$
(10)

In order for some of the magnetization to be non-zero after spatial averaging, assuming an integer number of turns of the magnetization helix along the sample axis over the height of the detection coil, one of the terms in Eq. (10) must be constant with respect to position, and therefore must have a net coefficient of zero for *s*. This requires

$$N = -k\frac{\gamma_S}{\gamma_I} \tag{11}$$

for there to be a signal. In our experiments, we usually select k = -1, which gives

$$M_{\rm DDF}^{I+} = i M_{\tau}^{I} \sin(\beta) \exp[i(\Delta\omega_{I}t_{2} - \Delta\omega_{S}t_{1})] J_{1} \left(-\frac{2}{3}\gamma_{I}\mu_{0}M_{\tau}^{S}t_{2}\right).$$
(12)

For a more intuitive description, one can say that if the M^{I+} magnetization is wound up as a helix along z with the same pitch as the helix of the S spin, i.e., $\gamma_S G_z T = \gamma_I G_z NT$, some of the crushed M^{I+} magnetization gets refocused because $B_d^S(s)$ has the same spatial dependence as M^{I+} .

With inductive detection, the signal is proportional to $\partial M_{\text{DDF}}^{l+}/\partial t_2$. Since detection is done in the laboratory frame, one has to convert M_{DDF}^{l+} into this frame as well, and we get

$$\frac{\partial M_{\text{DDF}}^{I+}}{\partial t_2} = M_{\tau}^I \sin(\beta) \exp(\omega_I t_2 - \Delta \omega_S t_1) \\ \times \left[\left(\omega_I + \frac{i}{t_2} \left(1 + \frac{t_2}{T_2^I} - \frac{t_2}{T_1^S} \right) \right) J_1 \left(\frac{2}{3} \gamma_I \mu_0 M_{\tau}^S t_2 \right) \right. \\ \left. - \frac{2i}{3} \left(1 - \frac{t_2}{T_1^S} \right) \gamma_I \mu_0 M_{\tau}^S J_0 \left(\frac{2}{3} \gamma_I \mu_0 M_{\tau}^S t_2 \right) \right] \\ \approx M_{\tau}^I \sin(\beta) \omega_I \exp[i(\omega_I t_2 - \Delta \omega_S t_1)] J_1 \\ \left. \times \left(\frac{2}{3} \gamma_I \mu_0 M_{\tau}^S t_2 \right) \right].$$
(13)

The approximation can be made because at high field the real part of the expression in square brackets, which is scaled with ω_I , is several orders of magnitude larger than the imaginary part except for very short t_2 , which are not relevant for the signal in our experiments. In the absence of relaxation, the maximum signal amplitude is not dependent on M_0^S , but only on M_0^J . Since the maximum of $J_n(x)$ is at $x \approx 1.84$, the position of the signal maximum is at

$$t_2 \approx \frac{2.75}{\mu_0 \gamma_I M_0^S \exp\left(-\frac{t_1}{T_2^S}\right)} = 2.75 \tau_d^I \exp\left(\frac{t_1}{T_2^S}\right),\tag{14}$$

where $\tau_d^I = (\mu_0 \gamma_I M_0^S)^{-1}$ is the characteristic dipolar demagnetizing time of spin *I* in the presence of the dipolar field of spin *S* [29].

As a next step, we have to reconsider the above assumption to neglect longitudinal relaxation of $M_z^S(s)$ during t_2 . Because M_z^S in the argument of J_1 relaxes with T_1^S , one does not get a pure Bessel shaped envelope of the signal, but something like a "stretched" Bessel. The part of M_z^S that is modulated along z, which is responsible for the refocusing of M^{I+} , diminishes until it finally reaches its limiting value when $M_z^S = M_0^S$. Therefore, it is usually not possible to observe the zero-crossing of the Bessel function. If we perform a series expansion of $J_1(Ax)$, where A is a constant and x is the variable term, we get

$$J_1(Ax) = \frac{1}{2}Ax - \frac{1}{16}A^3x^3 + \frac{1}{384}A^5x^5 + O(x^7).$$
 (15)

Usually even with large values of M_0^S it is still reasonable to only consider the lowest order term of this expression. Since this term is linear in A and x, we can simply determine the t_2 dependence of M_{τ}^S as

$$M_{\tau}^{S}(t_{2})t_{2} = \int_{0}^{t_{2}} M_{0}^{S} \exp\left(-\frac{t_{1}}{T_{2}^{S}} - \frac{t}{T_{1}^{S}}\right) dt$$
$$= M_{0}^{S} \exp\left(-\frac{t_{1}}{T_{2}^{S}}\right) \frac{T_{1}^{S}}{t_{2}} \left[1 - \exp\left(-\frac{t_{2}}{T_{1}^{S}}\right)\right] \qquad (16)$$

If we neglect instrumental constants, the signal becomes

$$s(t_2) = \frac{\partial M_{\text{DDF}}^{I+}}{\partial t_2} = -\frac{\mu_0}{3} \gamma_I^2 B_0 T_1^S \sin(\beta) M_0^I M_0^S \left[1 - \exp\left(-\frac{t_2}{T_1^S}\right) \right]$$
$$\times \exp\left(i\omega_I t_2 - \frac{t_2}{T_2^I}\right) \exp\left(-i\Delta\omega_S t_1 - \frac{t_1}{T_2^S}\right). \tag{17}$$

The maximum refocusing of M^{I+} for $t_2 \gg T_1^S$ gets delayed by the effect of the longitudinal relaxation on $M_z^S(t_2)$. The degree of refocusing of the *I* spins corresponds to the value it would have reached at $t_2 = T_1^S$ in the absence of T_1^S relaxation. On the other hand, as long as $t_2 \ll T_1^S$, we get

$$s(t_2) \approx -\frac{\mu_0}{3} \gamma_I^2 B_0 \sin(\beta) M_0^I M_0^S t_2 \exp\left(i\omega_I t_2 - \frac{t_2}{T_2^I}\right) \\ \times \exp\left(-i\Delta\omega_S t_1 - \frac{t_1}{T_2^S}\right).$$
(18)

129

Therefore as long as experiments are done in the linear regime of $J_1(2t_2/3\tau_d)$, which is fulfilled well if $t_2 < \tau_d$, the signal is bilinear in the analyte and the sensor magnetization.

With a non-transient detection method where the signal is read out at one particular point of the evolution during t_2 , we get the maximum signal amplitude at $t_2 = T_2^T$ as

$$|s^{\max}| = \frac{\mu_0}{3} \gamma_I^2 B_0 \sin(\beta) M_0^I M_0^S T_2^I \exp\left(-\frac{t_1}{T_2^S} - 1\right), \quad (19)$$

if $s(t_2)$ is given by Eq. (18).

So far, only the case has been discussed where the spectrum of the I spins and the spectrum of the S spins consist of one line each. For the sensor spins, this is a realistic assumption, and all the experiments presented here use a single-line sensor. But the S spins can very well have a more complicated NMR spectrum. In this case the trigonometric addition formula $\sum_{l} \cos(\Delta \omega_{S_l})$ $t_1 - \gamma_S G_z T s) = \cos(\gamma_S G_z T s) \sum_l \cos(\Delta \omega_{S_l} t_1) + \sin(\gamma_S G_z T s)$ $\sum_{l} \sin(\Delta \omega_{S_l} t_1)$, with *l* denoting the different spectral components of S, allows $\sum_{l} \cos(\Delta \omega_{S_l} t_1)$ and $\sum_{l} \sin(\Delta \omega_{S_l} t_1)$ to be incorporated into the argument of the Bessel function in Eq. (10). For $k = \pm 1$, this leads to a linear superposition of the signals from the S spins as long as the experiments are done in the linear regime of the Bessel function. Therefore the time-domain signal along t_1 matches the evolution of the S spins in a onepulse NMR spectrum.

An interesting feature of experiments with Xe dissolved in the analyte is that the two magnetization patterns experience the same \mathbf{B}_0 inhomogeneities. A B_0 dependent correlation between the I and S spins is obtained for k-space spectral components of the B_0 inhomogeneities smaller than λ^{-1} , which manifests itself as ridges in the 2D spectrum with a slope of $-k\gamma_S/\gamma_I$. The ridges can be straightened by a shearing transform or by a projection of the spectrum onto an axis perpendicular to the tilting axis of the lines [28], and the high-resolution spectrum of the analyte can be restored. When the Xe and the analyte are in different containers, such a correlation of inhomogeneities is usually much less effective because I and S spins do not occupy the same space. With a tube in a tube configuration, analyte and sensor only overlap along the z axis, which leaves only z inhomogeneities to be correlated. And with λ typically on the order of the diameter of the inner sample tube, only B_0 inhomogeneities with low k-space spectral components can be correlated, which can be shimmed out reasonably well anyway.

If the recycle delay time t_r between consecutive traces (i.e., between the detection pulse of one trace and the preparation pulse of the next trace) is on the order of T_1^S or shorter such that a considerable amount of modulated $M_z^S(s)$ does not relax, some of the S magnetization can evolve into double or zero quantum coherences. This can cause spectral artifacts along t_1 , which diminish with a time constant given by the combined effect of T_1^S and the diffusion time constant of the analyte helix along z. A strong spoiler gradient, which is usually applied to dephase residual M^+ magnetization after the acquisition, does not improve the situation because longitudinal magnetization is not affected by a gradient pulse. To avoid these artifacts, it is either necessary to wait several T_1^S between subsequent traces, to apply simultaneously a spoiler gradient and an rf saturation pulse on the S spins, or to design a phase cycle that considers coherences that build up over more than one transient [30].

2.2. Influence of radiation damping

The precession of a highly magnetized spin species induces an oscillating current in the receiver coil which is strong enough that the coil itself produces a transverse resonant magnetic field that causes a torque on the spins. This radiation damping can be quantitatively described as a modification to the Bloch equations [31]. The angle β between $\mathbf{M}(t)$ and the equilibrium magnetization \mathbf{M}_0 changes as

$$\frac{\mathrm{d}\beta}{\mathrm{d}t} = -\frac{\sin(\beta(t))}{\tau_{\mathrm{r}}} \tag{20}$$

with the characteristic rate of radiation damping $\tau_{\rm r}^{-1} = 2\pi Q \eta |\gamma| |\mathbf{M}(t)|$, where Q is the quality factor of the probe rf circuit and η is the filling factor of the rf coil. Usual strategies to prevent radiation damping involve detuning or overcoupling of the rf circuit, modifying the circuit to suppress radiation damping, or, if possible, apply only small tipping angle rf pulses. In our experimental scheme, another possibility to diminish radiation damping is to apply a gradient pulse immediately after the rf pulse, which averages out the integrated magnetization over the whole sample volume. However, recent studies have shown that the combination of radiation damping and the presence of a DDF from an abundant solvent nucleus at a high magnetic field can lead to turbulent spin dynamics [26] even if magnetization has been crushed directly after an rf pulse. This fact by itself would complicate DDF detection of NMR, even though the influence of instrumental and environmental magnetic noise has not been included in these studies. Fortunately, since in a heteronuclear experiment the encoding circuit is not used for detection, we are able to reduce its Q and detune it without losing sensitivity, as long as we still can apply pulses short enough to obtain the desired pulse bandwidth on the analyte spins. And because turbulence effects [32] accumulate during the course of an experiment, it is advisable to apply gradient pulses as late in the sequence as possible. On the detection side, radiation damping is of minor

importance because the pulse tipping angles are small, leading to only a small transverse component of **M**. Therefore, radiation damping will not be considered further in the following discussion.

2.3. Influence of multiplicative noise

Fluctuations of the environment of a sample that influence the propagator of a spin system lead to an error of the spin magnetization [33]. This noise is multiplicative. Fluctuations of \mathbf{B}_0 , which is denoted as \mathbf{B}_n in Eq. (3), is typically the dominant source of multiplicative noise (or t_1 noise) in liquid-state NMR experiments. Because $|\mathbf{B}_n| \ll |\mathbf{B}_0|$, the components of \mathbf{B}_n that are not parallel to \mathbf{B}_0 get truncated, and $\mathbf{B}_n \approx B_{n,z} \equiv B_n$. Even though B_n could be spatially inhomogeneous, it is spectrally homogeneous. All spins see the same environmental fluctuations, thus each signal component gets convoluted with the same noise contribution. Spin magnetization precessing in the transverse plane accumulates an additional phase contribution

$$M'^{+}(t) = M^{+}(t) \exp\left(-i\gamma \int_{0}^{t} B_{n}(t') dt'\right)$$

$$\approx M^{+}(t)[1 - \gamma B_{n}t], \qquad (21)$$

where $M'^+(t)$ is the transverse spin magnetization affected by multiplicative noise, and $M^+(t)$ is the noiseless quantity. The correlation time of B_n is low—typically on the order of t_2^{max} . Therefore during a transient evolution of magnetization, B_n can be approximated as being constant. This noise is affecting the *S* spins during t_1 and the *I* spins during t_2 . The phase error on the *S* spins gets converted into an amplitude error by the storage pulse. If we assume that B_n during t_1 is not correlated with B_n during t_2 , which might be somewhat oversimplified but is often a practical assumption, the two noise terms add in quadrature. The standard deviation σ_M of the multiplicative noise in the transient dimension can then be approximated by

$$\sigma_M(t_2) \approx \sqrt{\left(\gamma_S k \sigma_B t_1\right)^2 + \left(\gamma_I \sigma_B t_2\right)^2 |s(t_2)|}, \qquad (22)$$

where σ_B is the standard deviation of B_n . According to Eq. (17) the signal $s(t_2)$ in a DDF experiment is a product of a rising component and a decaying component; it reaches its maximum at $t_2 = T_2^l$. This causes an amplification of multiplicative noise compared to a free induction decay (FID), which depends on T_2^l , t_2^{max} , and the relative contribution of $(\gamma_S k \sigma_B t_1)^2$ to $(\gamma_I \sigma_B t_2)^2$. However, on-resonant this amplification is smaller than a factor two if both experiments use transient signal detection with the same t_2^{max} and no apodization. Only if t_2^{max} in the FID experiment can be kept short compared to t_2^{max} of a DDF experiment, this figure increases.

It might appear that the low γ of ¹²⁹Xe compared to, say, protons is an advantage, but since the refocusing of

the magnetization with a high γ sensor is faster, there is no net advantage of the low γ_I in this experiment. Multiplicative noise that adds during t_1 causes mainly problems when high spectral resolution is required with correspondingly long t_1 . If k in Eq. (11) is not equal to ± 1 , the noise can also increase substantially, as it gets scaled by |k| during t_1 .

Since there is usually no correlation of multiplicative noise between adjacent data points in an experiment with point-by-point detection, noise gets evenly distributed across the whole spectrum (white noise). If the same data set is detected directly, each line simply gets convoluted with the transient noise pattern, whose spectral density is on the order of the width of a typical line. Therefore a point-by-point experiment is affected stronger by multiplicative noise than an experiment with direct detection, where only the reproducibility is affected. The contribution of multiplicative noise can be estimated by comparing the noise level along the direct dimension of the spectrum with the noise level along the indirect dimension. Multiplicative noise only eventually limits the maximum signal-to-noise ratio (SNR), but it does not limit the minimum detectable analyte concentration. However, the noise caused by an intensive line can cover weak lines of the same analyte spectrum. Correspondingly, if the direct FID of ¹²⁹Xe is not fully dephased by the second gradient pulse, the remaining portion also contributes to the multiplicative noise, even if it is subtracted by a phase cycle.

Different measures can be taken to reduce multiplicative noise. B_0 fluctuations can be corrected with a frequency lock. Except for analytes with only a single NMR line it was usually very difficult to obtain a spectrum at all without frequency lock in our experiments. If the analyte spectrum consists of weak and strong lines that are well separated from each other and their positions are approximately known, one possibility to recover the full sensitivity for the weak lines is to apply semiselective pulses that do not excite the strong lines. Oversampling along the indirect dimension also improves the SNR [35], but this improvement is, at least for white noise, only proportional to the square root of the number of points and thus the detection time, and is therefore equivalent to signal averaging, except that it can be adjusted in finer steps. If the achievable SNR is eventually limited by multiplicative noise, β can be reduced until the additive SNR is about equal to the multiplicative SNR. Smaller β values allow to apply more pulses until all of the Xe polarization of a single batch is used up, which in turn improves the SNR.

2.4. Magnetization decay and diffusional mixing of xenon gas

During a batch mode experiment the polarization of ¹²⁹Xe continually diminishes because the equilibrium

polarization is orders of magnitude lower than the initial polarization. If all the xenon gas was in the active volume $V_{\rm C}$ of the transmitter coil, its longitudinal magnetization before the (n + 1)th pulse would be

$$M_{z}^{I}(t_{n+1}^{-}) = M_{z}^{I}(t_{n}^{-})\cos(\beta)\exp\left(-\frac{t_{r}+n\Delta t_{1}}{T_{1}^{I}}\right).$$
 (23)

The evolution time of the analyte increases by Δt_1 between consecutive transients. Since $t_{n+1} = nt_r + n(n+1)\Delta t_1/2$, Eq. (23) can be written as

$$M_{z}^{I}(t_{n+1}^{-}) = M_{0}^{I} \cos(\beta)^{n} \exp\left(-\frac{nt_{r} + n(n+1)\Delta t_{1}/2}{T_{1}^{I}}\right)$$
$$\approx M_{0}^{I} \exp\left[-n\left(\frac{\beta^{2}}{2} + \frac{t_{r}}{T_{1}^{I}}\right)\right].$$
(24)

The approximation is valid for $\beta \ll 1$ and $t_r \gg n\Delta t_1$. With constant flip angles β , the signal along the indirect dimension gets reduced in correlation to the drop of the magnetization. This acts like an apodization along t_1 and causes the line of the analyte to be broadened independently of the relaxation time, but dependent on Δt_1 and on β . The shorter Δt_1 , the broader the line in the indirect dimension of the spectrum becomes. The signal along t_1 decays as $|s(t_1)| = s_0 \exp(-t_1/\tau_1)$ with the lifetime

$$\tau_1 \approx \left[\frac{1}{T_2^s} + \frac{t_r}{T_1^l \Delta t_1} + \frac{\beta^2}{2\Delta t_1}\right]^{-1},\tag{25}$$

where the same approximations as for Eq. (24) were made. If the decay curve is known, such a line broadening can be corrected by either deconvoluting the spectrum or, equivalently, multiplying each time trace with the inverse of the decay function of $M_z^l(t_n)$. However, such a resolution enhancement generally reduces the sensitivity. Because at least for concentrated analytes the sensitivity at the beginning of the decay along t_1 is dominated by multiplicative noise, the apodization can be chosen that the noise is about equal to the additive noise. In a next step, an apodization for sensitivity enhancement like a matched filter can be applied. For example, a Lorentz-to-Gauss transform seems a very promising filter for this kind of data.

A better solution to avoid sensitivity loss and line broadening would be to determine a variable flip angle scheme [36] that leads to a constant signal during the experiment. The calculation of such a variable flip angle is considerably complicated by the fact that in the sample arrangement with the Xe gas in an inner tube and the analyte in an outer tube, $V_{\rm C}$ contains only a fraction of the total Xe volume. During the course of an experiment, the Xe inside and outside $V_{\rm C}$ are mixed by diffusion, which increases the apparent ¹²⁹Xe lifetime beyond what would be expected from the setting of β . The parameters that determine this decay include β , t_r , the self-diffusion constant D_{Xe} of the xenon gas, which itself depends on the pressure p of xenon (and possibly present inert gases), and the dimensions of the Xe container. A recursive relation can be obtained by assuming a sample tube that extends to infinity in one or both directions, and that t_r is long enough to level out the magnetization of the Xe gas inside V_C between subsequent traces of the experiment [37]. Experimentally it was found that the depletion of $M_z^I(t_n)$ can be fitted reasonably well using a stretched exponential

$$M_z^I(t_{n+1}^-) \approx M_0^I \exp\left(-\frac{t_1^{\alpha}}{\tilde{\tau}_1}\right),\tag{26}$$

where $\tilde{\tau}_1$ is the measured lifetime of the signal, and the exponent $\alpha < 1$ is responsible for a decay slower than monoexponential, especially for large *n*, since the more the xenon polarization gets depleted in the direct vicinity of V_C , the more important becomes diffusional mixing of small quantities of xenon gas over longer distances inside the sample tube.

2.5. Drifts of the xenon sensor resonance frequency

DDF experiments are very sensitive to drifts of the ¹²⁹Xe resonance frequency between different transients along the indirect dimension [38]. Such drifts can occur because of the large pressure and temperature dependence of the ¹²⁹Xe chemical shift, which was found to be [39]

$$\sigma = \sigma_0 + \sigma_1 \rho, \tag{27}$$

where ρ is the xenon density in amagat, and $\sigma_1 = -0.548$ ppm/amagat at 25 °C. Assuming the ideal gas law to be applicable, this leads to

$$\Delta \sigma \approx \left[-1.84 \times 10^{-3} \frac{\text{ppm}}{\text{K}} \right] \frac{p\Delta T}{p_0}$$
$$= \left[-0.0216 \frac{\text{Hz}}{\text{TK}} \right] \frac{p\Delta TB_0}{p_0}, \qquad (28)$$

where p is the pressure, p_0 is 1 atm (standard pressure), and ΔT is the temperature change for which the chemical shift change is calculated. This drift can be especially significant for experiments with pure xenon gas as sensor because of the low thermal conductivity of xenon of 56.9 μ W cm⁻¹ K⁻¹ at 25 °C and a pressure of 1 atm [40], which causes a very slow adaption of the xenon temperature to the temperature of its environment.

If pure xenon gas is used at a pressure of several bar, another reason for a shift of the ¹²⁹Xe resonance frequency could be the change of the self-demagnetizing field caused by the decreasing magnetization of hyperpolarized ¹²⁹Xe as sensor during an experiment. Due to the larger spin density compared to a gas, this effect would be considerable especially if liquid [23] or supercritical [8] xenon were used. If the xenon and the analyte are mixed, both experience the same demagnetizing field of the xenon, and the frequency shift can be corrected with a frequency lock. In the tube in a tube setup, however, the self-demagnetizing field of the Xe does not get corrected with the lock, but it is even amplified because its direction is opposite to the direction of the demagnetizing field that the analyte sees.

3. Experimental details

The experiments were performed on a Unity Inova spectrometer (Varian, Palo Alto CA) with a 7 T widebore magnet (Oxford Instruments, Cambridge, UK), corresponding to a proton frequency of 300 MHz. For the experiments with the Xe diluted inside the analyte a two channel 5 mm probe (Varian) was used (broadband channel inner, ${}^{1}H/{}^{19}F$ channel outer coil), which was equipped with a separate deuterium lock channel and a z gradient coil. The experiments were done by mixing the analyte and the Xe gas in a 5 mm outer diameter J-Young tube (Wilmad Labglass, Buena, NJ). A 10 mm probe (Varian) with two channels (a broadband channel using the inner coil, and a ¹H/¹⁹F channel using the outer coil), a separate deuterium channel for frequency locking, and a z gradient coil was used for the experiments with Xe and analyte in different containers. In principle there are no general restrictions regarding the geometry of the containers holding the analyte and the Xe. We used two coaxial NMR glass tubes with different diameters. The outer tube was a thick-walled 10 mm NMR sample tube (Wilmad) that contained the analyte. For Xe a 5 mm outer diameter J-Young tube with a wall thickness of 0.9 mm was used. It was stabilized inside the 10 mm tube with a plastic spacer (Fig. 2). The inside of the J-Young tube was coated with SurfaSil (Pierce, Rockford, IL) to increase the T_1 of ¹²⁹Xe. Inside the 7 T magnet, $T_1(^{129}Xe) \approx 50$ min was measured. The ratio of the Xe volume in the sensitive region of the coil compared to the total tube volume was about 1/13.

Spin-exchange optical pumping was done using a XenoSpin polarizer (Amersham Health, Durham, NC). A gas mixture of 1% naturally abundant Xe, 10% N₂, and 89% He (Spectra Gases, Vista, CA) was used. After polarization, the Xe was condensed into a cold finger immersed in liquid nitrogen. That way the inert gases were separated, and the experiments could be done with pure Xe gas. During thawing the gas was transferred into the J-Young tube. Immediately after removing the liquid nitrogen container, the cold finger with the frozen xenon was immersed in hot water (~80 °C) to accelerate thawing and therefore minimize the depolarization of ¹²⁹Xe. The Xe pressure in the sample tube was 3–5 bar, and the ¹²⁹Xe spin polarization was about 7%.



Fig. 2. Setup for the tube in a tube experiment. The analyte was in the outer tube, the sensor in the inner tube. The diameters of the inner and the outer tube were 5 and 10 mm, respectively. The wall thickness of the inner tube was 0.9 mm.

The pulse sequence is shown in Fig. 1. Since Xe cannot be refreshed during an experiment, pulses on ¹²⁹Xe with only small flip angles β had to be used to allow for a reasonable number of points in the analyte spectrum, which was recorded point-by-point. The length of the gradient pulses was fixed at 1 ms, and the gradient amplitude was modified for the different experiments. At the end of the detection period, a strong crusher gradient was applied to dephase remaining transverse magnetization. The field gradients do not just serve to break the symmetry of the sample, but also act as coherence pathway filters if they are strong enough [41]. However, as is shown later experimentally, with the tube in a tube setup optimal signal is obtained with rather weak gradients. The direct FID is only partially suppressed, and only incomplete frequency discrimination is achieved in the indirect dimension. Therefore the phase cycle shown in Table 1 was used.

To simplify the calibration of the setup, a model system was used in addition to the xenon experiments where hyperpolarized ¹²⁹Xe was replaced by ³¹P as the sensor nucleus—in particular, phosphoric acid (Fisher

 Table 1

 Phase cycle used for the tube-in-a-tube experiments

S pulse 1 (°)	S pulse 2 (°)	I pulse (°)	Receiver (°)
0	0	0	0
0	180	180	0
0	90	90	0
0	270	270	0

The first two steps remove the direct FID, and the second two steps select one coherence pathway to get frequency discrimination along ω_1 .

Scientific, Fair Lawn, NJ) has proved to be a sensible choice. $\gamma(^{31}\text{P})$ is only about 50% higher than $\gamma(^{129}\text{Xe})$, and both sensors have an NMR spectrum with only one single narrow line. This has the advantage that for quantifying the sensitivity, we do not have to consider all the additional imponderabilities of hyperpolarized gas like not perfectly reproducible polarization of ^{129}Xe between batches, or the continuous depletion and diffusion of Xe magnetization during the course of an experiment.

4. Sensitivity optimization

4.1. Gradient calibrations

An important parameter to optimize the sensitivity of DDF experiments is the gradient strength for maximum signal. A calibration experiment was done with phosphoric acid in the inner and benzene (Fisher Scientific) in the outer tube. The H_3PO_4 was mixed with D_2O (99% D, Aldrich Chemical, Milwaukee, WI) at a ratio of $H_3PO_4:D_2O = 1:2$, where the deuterium was used for frequency locking. In these experiments, ¹H was the analyte nucleus, and ³¹P was used as sensor. Fig. 3 shows the signal and noise as a function of the gradient strength for different delay times t_r between subsequent traces along t_1 . The gradient strength is given in relative units, where G_0 corresponds to a gradient that dephases the magnetization by one period over a distance λ equal to the outer diameter d of the inner sample tube. In Fig. 3A, t_r is shorter than T_1 of ³¹P, and in Fig. 3B, t_r is about $2T_1(^{31}P)$. The signal of the ¹H line of phosphoric acid as a function of G_z is completely different in these two cases. The benzene signal shows the same qualitative behavior in both cases, but the fact that the signal decays to a lower value for the second case leads to the assumption that not only the signal, but also the noise level is considerably different in these two experiments. The lower graphs of Fig. 3 show the noise level at some arbitrary frequency and at $\Delta \omega = 0$, where no signal is expected with the particular choice of the reference frequency ω_0 . The scales in the upper and the lower graphs of Fig. 3A are identical, while the lower graph of Fig. 3B is scaled up by a factor five compared to the upper. If t_r is short compared to $T_1({}^{31}\text{P})$, noise can be inherited between different repetitions of the experiment. This mechanism might be one reason for the higher noise amplitude in Fig. 3A compared to Fig. 3B, especially in combination with either radiation damping or interaction with the transverse dipolar field of other ³¹P nuclei, which acts much like a weak pulse or radiation damping [20]. The phase cycle to remove unwanted coherences leaves a signal at $\Delta \omega_S = 0$ of considerable intensity in Fig. 3A, because it was not designed to remove coherence pathways of magnetization evolving

Fig. 3. Signal and noise of a DDF detected ¹H NMR spectrum of benzene as a function of the magnetization modulation wavelength using a separated ³¹P sensor in a coaxial tube geometry. A four-step phase cycle was employed to suppress the direct ³¹P FID and to ensure frequency discrimination in the indirect dimension. The ratio of the two gradient pulses was fixed to the value $N = -\gamma_{1H}/\gamma_{31P} = -2.47.64$ points along the indirect dimension were taken. $G_z/G_0 = d/\lambda$ denotes the strength of a z-gradient pulse, relative to a gradient pulse $G_0 = 2\pi/2$ $|\gamma T d|$ that would modulate the same nucleus by one wavelength over d = 0.5 cm. A 4 ms long, 22 G/cm z-gradient spoiler pulse preceded each delay between experiments. (A) $t_r = 2 s$ delay time between experiments. (B) $t_r = 6$ s between experiments. (Upper) Signal as a function of gradient strength. Data points of the ¹H signal due to H₃PO₄ and C₆H₆ are connected by a solid and a dashed line, respectively. (Lower) Noise as a function of gradient strength. (Dotted line) Average noise level at frequencies with no signal and $\Delta \omega$ neq 0. (Dash-dotted line) Noise level at $\Delta \omega = 0$.

4

5

2 3

 G_{f}/G_{0}

longer than just during one trace [30]. This is also a reason for the much higher signal with low G_z at $\Delta \omega_S = 0$ from the same nuclei in Fig. 3A than in Fig. 3B. If the direct FID of ³¹P is incompletely suppressed with a field gradient and the reason is not systematic, it causes an increased noise level over the whole frequency range along t_1 . Since this noise source is independent of the signal induced by intermolecular multi-quantum transitions, it does not appear to be multiplicative. Nevertheless, the noise level along the indirect dimension is considerably higher than along the direct dimension, which is indicative for t_1 noise.

Another important parameter to describe the sensitivity of DDF experiments with a tube in a tube configuration is the geometrical factor or filling factor, which can be defined as the ratio of the field seen by the sensor versus the field the sensor would see if it were dissolved in the analyte at infinite dilution. To analytically determine this ratio is very difficult and can be done with satisfying accuracy only for situations that are not really relevant for viable setups. But an experimental determination is straightforward and can be done with the data



A

Signal (a.u.)

0

Noise (a.u.)

3

 G_{f}/G_{0}

2

from the previous paragraph. H_3PO_4 (85 wt% in H_2O) has a total proton density of 72.4 mol 1 H/L, while benzene has 67.6 mol/L protons. Both spectra show only a single line, phosphoric acid because of fast proton exchange with water, and benzene because the protons are equivalent. As the phosphoric acid was diluted with D_2O_2 , its effective proton density is about 24 mol/L. If the signal is taken at the maximum of the benzene peak, an optimum geometrical factor of about 0.35 is obtained for the setup described above. However, as can be seen best from Fig. 3B, the geometrical factor strongly depends on G_z and rapidly decays towards a very small value for λ shorter than the diameter of the inner tube. Note that this result is not in contradiction to the results in [42]. A modulated magnetization distribution creates a strongly modulated Lorentz sphere corrected DDF within the source volume, which is relevant for homogeneous mixtures, but a self-cancelling DDF external to the source volume, which is relevant for tube in a tube experiments.

The above discussion shows the difficulty to compare the sensitivity between DDF experiments and transient one-dimensional (1D) NMR experiments, because the two methods not only show a different signal behavior, but they are also limited by different noise mechanisms. Finally, in both cases the additive, i.e., signal independent, noise from the detector represents the ultimate limit. But with indirect detection, considerably more noise sources have to be considered, making an optimum choice of parameters noticeably more difficult.

4.2. Multiplicative noise

Multiplicative noise is caused by low-frequency fluctuations that get convoluted with the signal. Therefore each noise source affects all of the spins in the same way, thus each spin gets convoluted with the same noise pattern, and the noise has the same characteristics as the signal on which it is superimposed. That multiplicative noise is an important sensitivity limiting factor is shown in Fig. 4, where a ¹⁹F NMR experiment of 2,2,2-trifluoroethanol (99+%, Aldrich) with ³¹P of phosphoric acid as sensor was performed. No frequency locking was employed. A two step phase cycle was used to eliminate the direct FID, and the recycle delay was set to 6.5 s. One can see that the noise shows ridges parallel to the main feature of the ¹⁹F triplet, while the noise intensity is parallel to v_1 , which is characteristic for multiplicative noise. The dominance of multiplicative noise along the indirect dimension can also be seen by comparing the noise level of the two traces through the spectrum in Fig. 4.

If a spectrum in the indirect dimension consists of more than one line, multiplicative noise from the individual lines adds in quadrature. Therefore applying selective or semiselective pulses to excite only selected transitions reduces multiplicative noise, especially of



Fig. 4. DDF-detected ¹⁹F NMR spectrum of CF₃CH₂OH at 7 T, detected with ³¹P (85 % H₃PO₄) as sensor. The phosphoric acid was kept in a tube inside the analyte tube. v_1 is the offset from the ¹⁹F carrier, and v_2 is the offset from the ³¹P carrier. The white lines show the position of the traces through the spectrum shown above and beneath the 2D plot.

weak lines. Fig. 5 shows a ¹H NMR spectrum of a 3:2:1 mixture of isopropanol:phosphoric acid (85 %):D₂O. A DDF-detected spectrum with ³¹P as sensor was recorded with non-selective pulses and compared to spectra with selective pulses, where only a certain group of lines was excited at a time. The excitation pulse on the analyte was Gauss shaped with a width of 8.2 ms, the storage pulse was a 3 ms rectangular pulse. While the sensitivity of the methyl protons was not improved considerably with selective excitation, the SNR of the septet could be significantly improved with selective pulses.



Fig. 5. DDF-detected ¹H NMR spectrum of isopropyl alcohol at 300 MHz, detected with ³¹P as sensor. The sample was a 3:2:1 mixture of isopropanol:H₃PO₄ (85 %):D₂O. (A) Comparison of the sensitivity of the septet with selective (upper) and non-selective (lower) excitation. (B) Comparison of the sensitivity of the doublet with selective (upper) and non-selective (upper) and non-selective pulses.

5. Results

5.1. Xe in solution

For batch mode experiments, Xe was brought into the gas phase above the analyte, and the sample was shaken for about 10 s prior to the beginning of the experiment to ensure that Xe was saturated in solution. As an example, Fig. 6 shows a ¹H NMR spectrum of deuterated ethyl alcohol (C₂H₅OD, Aldrich). The Xe pressure in the gas phase inside the sample tube was 4.6 bar. 256 points were taken along t_1 . Because T_1 of ¹²⁹Xe in ethanol is about 160 s [43], it was necessary to set $t_r = 1$ s, which is less than T_1 of C₂H₅OD. The total acquisition time was 5 min. The pulse flip angle on the ¹²⁹Xe was adjusted carefully such that the noise level along the direct dimension, which is mainly due to thermal noise in the detection circuit, matches the multiplicative noise along the indirect dimension. In that way, the number of traces could be maximized, giving an optimum overall SNR. The first gradient pulse had an amplitude of 6.1 G/cm, and the second one was set to 22 G/cm. This caused a helix pitch of $\lambda \approx 0.39$ mm, which was enough to suppress the direct FID and select one coherence pathway of the I spin magnetization. Therefore no phase cycle was applied. This also helped to reduce multiplicative noise, because the direct FID was dephased and did not contribute. On the other hand, multiplicative noise was increased because some of it was inherited between subsequent traces due to the short t_r that did not allow all of the analyte magne-



Fig. 6. DDF-detected ¹H NMR spectrum of deuterated ethyl alcohol (C₂H₅OD) at 7 T, detected through ¹²⁹Xe as a sensor, which was mixed with the analyte. (A) Full ¹H NMR spectrum. (B) Enlargement of the quartet signal from the CH₂ group. (C) Pseudocolor plot of the triplet from the CH₃ group. v_1 is the indirect dimension, showing the ¹H spectrum, and v_2 represents the direct dimension, which is the ¹²⁹Xe NMR spectrum.

J. Granwehr et al. | Journal of Magnetic Resonance 176 (2005) 125-139

With one batch of hyperpolarized xenon, several independent experiments could be performed by reshaking the sample, such that fresh hyperpolarized Xe gas got dissolved in the analyte. In the case of C_2H_5OD , where one experiment was short compared to the T_1 of ¹²⁹Xe in the gas phase, a second experiment with only a small decrease of sensitivity could be done immediately after the first one.

5.2. Tube in a tube experiments

Fig. 7 shows a DDF-detected ¹H NMR spectrum of water in a field of 7 T, detected with hyperpolarized ¹²⁹Xe. A four step phase cycle was applied, and the recycle delay was set to 3 s. No frequency lock was used. In this experiment, the polarization of ¹²⁹Xe was only about 1%, and the pressure of the Xe gas was about 2 bar. The pulses on the ¹²⁹Xe had a flip angle of about $\pi/8$. Fig. 7A shows the absolute value of the signal along the direct dimension, and Fig. 7B shows the signal decay along the indirect dimension. The data along the indirect dimension was analyzed by fitting Eq. (26). The product



Fig. 7. DDF-detected spectrum of H₂O at 300 MHz, detected with ¹²⁹Xe as sensor. The Xe was kept in a tube inside the analyte tube. (A) Average signal amplitude along the direct dimension. The signal is a product of a rising component due to the effect of the DDF and a decaying component caused by transversal relaxation of ¹²⁹Xe. (B) Signal decay along the indirect dimension. Because of the depletion of the ¹²⁹Xe magnetization, the signal decays faster than T_2 of H₂O. (C) ¹H NMR spectrum after apodization with the inverse of the signal decay and an exponential decay to remove the arising noise at long t_1 values.

of the inverse of this function with an exponential decay with time constant $\tau = 24$ ms was used to apodize the data along t_1 before the Fourier transform.

Another experiment was done using *p*-ethoxybenzaldehyde (p–EBA, 99%, Aldrich). 25 vol.% d₅-pyridine (99+%, Wilmad) was admixed for frequency locking. The xenon pressure was 2 bar. The pulses on the 129 Xe had a flip angle of $\beta \approx 4^{\circ}$, which was determined in a separate experiment as being a reasonable choice to get a multiplicative noise level on the same order as the additive noise. The first gradient pulse had an amplitude of 0.078 G/cm, and the second one was -0.284 G/ cm. These gradients were not sufficient to select one coherence pathway, so in addition a two-step phase cycle was used to suppress the direct FID of ¹²⁹Xe, consisting of the first two steps in Table 1. But no frequency discrimination was performed in the indirect dimension, so a mirror spectrum is obtained at the negative frequency. The spectral width was chosen big enough to have all NMR lines in one half of the spectrum. Fig. 8A shows the data in a 2D representation of the analyte vs. the sensor frequency without apodizing the signal along t_1 prior to the Fourier transform. This experiment illustrates well the problems mentioned in Section 2. The experimental procedure was optimized to minimize the time between thawing of the xenon and the start of the data acquisition. Because of the hot water used for the thawing, at the beginning of the experiment the xenon gas was several degrees warmer than the ambient temperature, causing a drift of the ¹²⁹Xe resonance frequency of about 1.7 Hz. This drift, which is shown in Fig. 8D, and the accelerated apparent relaxation due to the diminishing ¹²⁹Xe polarization cause an asymmet-

ric line. Fig. 8B compares the experimental lineshape with a simulation using Eqs. (17) and (26). The lineshapes agree qualitatively, which shows that the model presented in Section 2 is adequate to describe the observed signal. The exact lineshape in this experiment depends on the temperature evolution and the corresponding t_1 dependence of the ¹²⁹Xe chemical shift. On the other hand, the frequency shift caused by the self-dipolar field of ¹²⁹Xe should be smaller than 0.1 Hz at this pressure. One can see in Fig. 8A that the lines are only symmetric with respect to $\omega_1 = 0$ at frequencies of ω_2 where the temperature was stabilized (Fig. 8C). During the drift of ω_I , the lines on both sides of the spectrum shift in the same direction, which could also be reproduced by the simulation. Fig. 8C shows a spectrum where the effect of the drift of ω_2 was corrected numerically prior to Fourier transform along the indirect dimension. All the available data points were used, yet it was possible to retain a linewidth that was given by the spectral resolution and an exponentially decaying apodization function with a time constant of 50 ms, after the signal was first multiplied with the inverse function of the signal decay.

5.3. Tip mode experiments

In this class of experiments, a signal builds up because of the asymmetry of the sample and the Xe container. In our experiments with a tube of xenon gas inside the tube with the analyte, this leaves several options like not pushing the tubes all the way down in the probe so they cannot be considered infinitely long, by having the inner tube only half way inside the



Fig. 8. DDF-detected ¹H NMR spectrum of *p*-ethoxybenzaldehyde at 300 MHz, detected with ¹²⁹Xe as sensor. (A) Contour plot of the full spectrum. (B) Close up of one line (left) and a simulation of the lineshape (right). For this simulation a drift $\Delta \omega_I = 2$ Hz was assumed. (C) ¹H spectrum after correcting for the drift of the ¹²⁹Xe resonance frequency. (D) Resonance frequency of ¹²⁹Xe as a function of t_1 . Only a Fourier transform along the direct dimension was performed, and the absolute value of the resulting spectrum was plotted. The gray line corresponds to a fit of the resonance frequency drift, which was used to obtain the spectrum in (C).



Fig. 9. DDF-detected ¹H NMR spectrum of a two-phase mixture of water and methyl acetate at 300 MHz. v_1 is the offset from the ¹H carrier.

excitation coil, or by having an analyte that is a multiphase mixture. In this experiment, the direct FID of the ¹²⁹Xe was suppressed using the first two steps of the phase cycle in Table 1. No phase cycle for frequency discrimination was applied. Instead the spectral width was chosen broad enough that the NMR spectrum fits in half of the bandwidth along ω_1 . This helps to distinguish signals from artifacts at or near $\Delta \omega_S = 0$. Fig. 9 shows a spectrum of a two-phase mixture of water/ D_2O (1:1) and methyl acetate (Fisher Scientific). The phase boundary between them was approximately in the center of the coils.

6. Discussion

We have demonstrated that heteronuclear intermolecular multiquantum coherences can be used to detect the NMR spectrum of an analyte through ¹²⁹Xe, which can be mixed with the analyte or in a different container. In "gradient mode" the interaction distance between xenon and proton spins can be experimentally set via the gradient strength [16]. However, the effect of washing out the xenon signal due to fast diffusion in between the two gradient pulses has to be considered. Furthermore, with the tube in a tube setup the gradient modulation wavelength λ must be on the order of the diameter of the inner tube or longer to avoid averaging out of the helical B_d distribution that Xe sees from the analyte. In "tip mode" the spatial origin of the detected signal reflects the homogeneity of the magnetic field produced by the protons around the xenon tube.

Keeping the xenon and the analyte in different containers has the advantage of being cleaner to use. It is possible to analyze potentially dangerous or highly sensitive substances while keeping them in a closed environment. Furthermore, the experimental conditions are less dependent on the substance to be analyzed. To mix analyte and sensor has the advantage that the correlation distance of analyte and Xe can be kept small by reducing λ , which allows the recovery of homogeneous linewidths by shearing of the spectrum. Additionally, the sensor feels the full demagnetizing field of the analyte. When the analyte and sensor are separated, a geometrical factor has to be considered that is equivalent to a filling factor in conventional experiments; it depends on the geometry of the setup and the magnetic susceptibility gradients between the involved materials like the container walls, which also makes the tube in a tube setup more difficult to shim.

The resolution that can be obtained with DDF encoding is comparable to high-resolution spectra with direct detection. Homonuclear J couplings can be resolved in a DDF detected spectrum also with a tube in a tube setup, as can be seen in Fig. 4. But the depletion of the magnetization causes an artificial broadening of the line in the indirect dimension, which does not depend on the inherent linewidth of the analyte. Apodization can correct for that to a certain extent, but at the expense of a reduced sensitivity. Recording the data with decreasing t_1 , starting with the longest value t_1^{max} , can improve the sensitivity, but requires a careful choice of t_1^{max} . A variable flip angle scheme to obtain a constant signal would improve the lineshape and also the sensitivity. However, the simple equations for variable flip angles that do not account for diffusional mixing [36] are unsatisfactory, at least for tube in a tube experiments.

For the Xe in solution experiments one sensitivity limiting factor was the low solubility of Xe in polar analytes. The gas exchange between the gas phase and the liquid was too slow to get considerable refreshing of Xe in solution on the time scale of the experiment. Furthermore doping the analyte with a paramagnetic relaxation agent is not possible because such a dopant would reduce the T_1 of ¹²⁹Xe as well. For the tube-in-a-tube experiments, on the other hand, a substantial reserve volume of gas outside the sensitive volume of the coil was available, and the continuous refreshing of gas allowed for higher flip angles. Additionally the total experiment time could be optimized by doping the analyte with a paramagnetic salt.

The examples shown in this report were all done in batch mode. A different possibility would be to use a stopped flow mode where the Xe is replaced between different repetitions of the experiment. The continuously replaced magnetization allows for large pulse angle excitation and ideally makes the same initial magnetization available for each t_1 increment. This would also allow to record an unrestricted number of data points for the spectrum of the heteronucleus. And even though the magnetization of the gas is lower in flow mode than in batch mode as co-added inert gases are also circulated without preceding purification, the signal in both modes

can be about comparable, since all the available magnetization can be used up in each experiment in stopped flow mode. In batch mode there are no polarization fluctuations due to slow changes of the optical pumping environment, which might be a problem in flow mode. However, preliminary experiments in stopped flow mode did not show any results. This could be explained by an increased self-diffusion of the xenon gas, since the experiment was done using the optical pumping gas mixture containing 89% He and 10% N₂, which are both fast diffusing compared to xenon. If during detection the gas diffuses over a distance larger than the helix pitch created during encoding, no net magnetization will refocus due to the influence of the distant dipolar field of the analyte. This problem could be circumvented by either use a gas mixture with a high fraction of xenon [44], or prepolarize a batch of xenon, which is used up only in small fractions at a time.

Another alternative to batch mode would be to polarize Xe inside the magnet [45]. Since Xe and analyte can be kept in different containers, it is possible to admix Rb, which is necessary for optical pumping, to the container with the Xe. The T_2 of ¹²⁹Xe can still be very long, even in the presence of Rb [46], which enables experiments with alternating pumping and probing of Xe magnetization.

From the experiments done in this study, we can conclude that this technique would in principle be feasible in combination with remote detection. Remote detection would allow to use a smaller detection coil with a higher sensitivity, enabling the use of much smaller volumes of xenon gas per detection step. No spectral artifacts would be present due to the slow depletion of the xenon magnetization. However, gas mixtures with a high percentage of xenon gas would have to be used to minimize the self-diffusion of the sensor. Since configurations are possible where the analyte never gets in contact with the sensor, a setup with circular flow can be set up [47], allowing an economical use of xenon gas, so that even enriched ¹²⁹Xe could be considered. One problem of a remote experiment is the high vulnerability for multiplicative noise, which requires a very stable magnetic field, thus limiting the applicability with non-superconducting magnets. Other problems might arise due to the strong dependence on a stable flow. One has to wait with the encoding step until the gas has settled after stopping the flow, otherwise the sensitivity is reduced like in the case of high diffusion, prolonging the experiment considerably.

Acknowledgments

The authors thank Tanya Mazur and Megan Spence, who were involved in an early stage of this project, Janette Ruiz for her help with the polarizer, Sandra Garcia, Lana Chavez, and Song-I Han for the possibility to use their stopped flow setup, and Jamie Walls for insightful discussions. This work was supported by the Director, Office of Science, Office of Basic Energy Sciences, Materials Sciences and Nuclear Science Divisions, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098. J.G. gratefully acknowledges the Swiss National Science Foundation for support through a postdoctoral fellowship.

References

- B. Goodson, Nuclear magnetic resonance of laser-polarized noble gases in molecules, materials, and organisms, J. Magn. Reson. 155 (2002) 157–216.
- [2] S.M. Rubin, M.M. Spence, I.E. Dimitrov, E.J. Ruiz, A. Pines, D.E. Wemmer, Detection of a conformational change in maltose binding protein by Xe-129 NMR spectroscopy, J. Am. Chem. Soc. 123 (2001) 8616–8617.
- [3] A. Bifone, Y.-Q. Song, R. Seydoux, R.E. Taylor, B.M. Goodson, T. Pietrass, T.F. Budinger, G. Navon, A. Pines, NMR of laserpolarized xenon in human blood, Proc. Natl. Acad. Sci. USA 93 (1996) 12932–12936.
- [4] T. Meersmann, J.W. Logan, R. Simonutti, S. Caldarelli, A. Comotti, P. Sozzani, L.G. Kaiser, A. Pines, Exploring single-file diffusion in one-dimensional nanochannels by laser-polarized Xe-129 NMR spectroscopy, J. Phys. Chem. A 104 (2000) 11665–11670.
- [5] S.M. Rubin, M.M. Spence, A. Pines, D.E. Wemmer, Characterization of the effects of nonspecific xenon-protein interactions on Xe-129 chemical shifts in aqueous solution: further development of xenon as a biomolecular probe, J. Magn. Reson. 152 (2001) 79– 86.
- [6] M.M. Spence, S.M. Rubin, I.E. Dimitrov, E.J. Ruiz, D.E. Wemmer, A. Pines, S.Q. Yao, F. Tian, P.G. Schultz, Functionalized xenon as a biosensor, Proc. Natl. Acad. Sci. USA 98 (2001) 10654–10657.
- [7] G. Navon, Y.-Q. Song, T. Rõõm, S. Appelt, R.E. Taylor, A. Pines, Enhancement of solution NMR and MRI with laserpolarized xenon, Science 271 (1996) 1848–1851.
- [8] J.C. Leawoods, B.T. Saam, M.S. Conradi, Polarization transfer using hyperpolarized, supercritical xenon, Chem. Phys. Lett. 327 (2000) 359–364.
- [9] M. Luhmer, B.M. Goodson, Y.-Q. Song, D.D. Laws, L. Kaiser, M.C. Cyrier, A. Pines, Study of xenon binding in cryptophane-A using laser-induced NMR polarization enhancement, J. Am. Chem. Soc. 121 (1999) 3502–3512.
- [10] T. Brotin, A. Lesage, L. Emsley, A. Collet, Xe-129 NMR spectroscopy of deuterium-labeled cryptophane-A xenon complexes: Investigation of host-guest complexation dynamics, J. Am. Chem. Soc. 122 (2000) 1171–1174.
- [11] Y.-Q. Song, B.M. Goodson, R.E. Taylor, D.D. Laws, G. Navon, A. Pines, Selective enhancement of NMR signals for alphacyclodextrin with laser-polarized xenon, Angew. Chem. Int. Ed. Engl. 36 (1997) 2368–2370.
- [12] T. Rõõm, S. Appelt, R. Seydoux, E.L. Hahn, A. Pines, Enhancement of surface NMR by laser-polarized noble gases, Phys. Rev. B 55 (1997) 11604–11610.
- [13] A.J. Moulé, M.M. Spence, S. Han, J.A. Seeley, K.L. Pierce, S.K. Saxena, A. Pines, Amplification of xenon NMR and MRI by remote detection, Proc. Natl. Acad. Sci. USA 100 (2003) 9122– 9127.
- [14] J.A. Seeley, S. Han, A. Pines, Remotely detected high-field MRI of porous samples, J. Magn. Reson. 167 (2004) 282–290.

- [15] W.S. Warren, W. Richter, A.H. Andreotti, B.T. Farmer, Generation of impossible cross-peaks between bulk water and biomolecules in solution NMR, Science 262 (1993) 2005–2009.
- [16] W. Richter, S.H. Lee, W.S. Warren, Q.H. He, Imaging with intermolecular multiple-quantum coherences in solution nuclear magnetic resonance, Science 267 (1995) 654–657.
- [17] R. Bowtell, Indirect detection via the dipolar demagnetizing field, J. Magn. Reson. 100 (1992) 1–17.
- [18] M.P. Augustine, K.W. Zilm, Observation of bulk susceptibility effects in high-resolution nuclear magnetic resonance, J. Magn. Reson. A 123 (1996) 145–156.
- [19] K.W. Zilm, Optically pumped NMR in high magnetic fields, American Physical Society Meeting, Pittsburgh PA, USA, 1994.
- [20] W.S. Warren, S. Ahn, The boundary between liquidlike and solidlike behavior in magnetic resonance, J. Chem. Phys. 108 (1998) 1313–1325.
- [21] P.R. Bachiller, S. Ahn, W.S. Warren, Detection of intermolecular heteronuclear multiple-quantum coherences in solution NMR, J. Magn. Reson. A 122 (1996) 94–99.
- [22] M.P. Augustine, Ph.D. Dissertation, Yale University, 1995.
- [23] A.S. Verhulst, O. Liivak, M.H. Sherwood, I.L. Chuang, A rapid and precise probe for measurement of liquid xenon polarization, J. Magn. Reson. 155 (2002) 145–149.
- [24] I.E. Dimitrov, E. Insko, R. Rizi, J.S. Leigh, Indirect detection of lung perfusion using susceptibility-based hyperpolarized gas imaging, J. Magn. Reson. Imag. 21 (2005) 149–155.
- [25] S. Lee, W. Richter, S. Vathyam, W.S. Warren, Quantum treatment of the effects of dipole-dipole interactions in liquid nuclear magnetic resonance, J. Chem. Phys. 105 (1996) 874– 900.
- [26] S. Huang, Y.-Y. Lin, N. Lisitza, W.S. Warren, Signal interferences from turbulent spin dynamics in solution nuclear magnetic resonance spectroscopy, J. Chem. Phys. 116 (2002) 10325–10337.
- [27] A.L. Zook, B.B. Adhyaru, C.R. Bowers, High capacity production of >65% spin polarized xenon-129 for NMR spectroscopy and imaging, J. Magn. Reson. 159 (2002) 175–182.
- [28] R.R. Ernst, G. Bodenhausen, A. Wokaun, Principles of nuclear magnetic resonance in one and two dimensions, Clarendon Press, Oxford, 1987.
- [29] W. Richter, W.S. Warren, Intermolecular multiple quantum coherences in liquids, Concepts Magn. Reson. 12 (2000) 396–409.
- [30] N. Murali, A. Kumar, Multiple-quantum artifacts in singlequantum two-dimensional correlated NMR spectra of strongly coupled spins, Chem. Phys. Lett. 128 (1986) 58–61.
- [31] N. Bloembergen, R. Pound, Radiation damping in magnetic resonance experiments, Phys. Rev. 95 (1954) 8–12.

- [32] S.Y. Huang, J.D. Walls, Y. Wang, W.S. Warren, Y.-Y. Lin, Signal irreproducibility in high-field solution magnetic resonance experiments caused by spin turbulence, J. Chem. Phys. 121 (2004) 6105–6109.
- [33] A.F. Mehlkopf, D. Korbee, T.A. Tiggelman, R. Freeman, Sources of t₁ noise in two-dimensional NMR, J. Magn. Reson. 58 (1984) 315–323.
- [35] J.M. Nuzillard, R. Freeman, Oversampling in two-dimensional NMR, J. Magn. Reson. A 110 (1994) 252–256.
- [36] L. Zhao, R. Mulkern, C.-H. Tseng, D. Williamson, S. Patz, R. Kraft, R.L. Walsworth, F.A. Jolesz, M.S. Albert, Gradient-echo imaging considerations for hyperpolarized ¹²⁹Xe MR, J. Magn. Reson. B 113 (1996) 179–183.
- [37] J.T. Urban, Ph.D. Dissertation, University of California at Berkeley, 2004, http://www-library.lbl.gov/docs/LBNL/567/68/ PDF/LBNL-56768.pdf.
- [38] H.T. Edzes, The nuclear magnetization as the origin of transient changes in the magnetic field in pulsed NMR experiments, J. Magn. Reson. 86 (1990) 293–303.
- [39] C.J. Jameson, K. Jameson, S.M. Cohen, Temperature and density dependence of ¹²⁹Xe chemical shift in xenon gas, J. Chem. Phys. 59 (1973) 4540–4546.
- [40] R.C. Weast, Handbook of chemistry and physics, 54th ed., CRC Press, Cleveland, 1973.
- [41] G. Bodenhausen, H. Kogler, R.R. Ernst, Selection of coherencetransfer pathways in NMR pulse experiments, J. Magn. Reson. 58 (1984) 370–388.
- [42] W.S. Warren, S. Lee, W. Richter, S. Vathyam, Correcting the classical dipolar demagnetizing field in solution NMR, Chem. Phys. Lett. 247 (1995) 207–214.
- [43] S. Månsson, E. Johansson, J. Svensson, L.E. Olsson, F. Ståhlberg, J.S. Petersson, K. Golman, Echo-planar MR imaging of dissolved hyperpolarized ¹²⁹Xe, Acta Radiol. 43 (2002) 455–460.
- [44] R. Wang, R.W. Mair, M.S. Rosen, D.G. Cory, R.L. Walsworth, Simultaneous measurement of rock permeability and effective porosity using laser-polarized noble gas NMR, Phys. Rev. E 70 (2004) 026312.
- [45] M.P. Augustine, K.W. Zilm, Optical pumping magnetic resonance in high magnetic fields: characterization of nuclear relaxation during pumping, J. Chem. Phys. 105 (1996) 2998–3011.
- [46] D. Raftery, H.W. Long, D. Shykind, P.J. Grandinetti, A. Pines, Multiple-pulse nuclear magnetic resonance of optically pumped xenon in a low magnetic field, Phys. Rev. A 50 (1994) 567–574.
- [47] K. Knagge, J. Prange, D. Raftery D, A continuously recirculating optical pumping apparatus for high xenon polarization and surface NMR studies, Chem. Phys. Lett. 397 (2004) 11–16.